



## COUPLINGS - SCREW TYPE HOSE CONNECTION

Specifications
Screw type fittings are used to quickly couple machines to our range of WRE mining hoses from 10mm to 50mm
Smaller sizes are manufactured from mild steel, but where possible, use is made of ductile iron castings
These three-piece connections, which comprise a Spud, Wing nut and Hose tail with gasket, are simple and reliable
A superior grade of neoprene is used for the sealing gasket which is located on the hose tail spigot
Interchangeability at the lower end of the range is a feature. This ensures a combination of pipe thread and hose sizes to suit all needs
Although originally designed for air and water they are suitable for all mildly corrosive gasses or liquids
Complies to SANS1086 pressure requirements



Type	Hose Size (mm)	Pipe Thread B.S.P.	Description	Item Number
12.5mm Light Screw Type	-	3/8" Male	Spud	5980
	-	1/2" Male	Spud	267
	-	3/4" Male	Spud	288
	-	1" Male	Spud	26500
	-	3/8" Female	Spud	270
	-	1/2" Female	Spud	269
	-	3/4" Male	Backhead Spud with Gland Nipple	6055
	-	-	Gland Nipple	231
	10	-	Hosetail with Gasket	259
	10	-	Hosetail with Gasket with 4,0mm Hole	11313
	12,5	-	Hosetail with Gasket	258
	12,5	-	Hosetail with Gasket with 4,5mm Hole	11310
	12,5	-	Hosetail with Gasket with 3,0mm Hole	11457
	-	-	Wing Nut	864
-	-	Gasket	335	
12.5mm Light Airtite Screw Type	-	1/2" Male	Spud	272
	-	1" Male	Spud	182
	-	1/2" Female	Spud	284
	12,5	-	Hosetail	257
	-	-	Wing Nut	864
25mm Screw Type	-	3/4" Male	Spud	276
	-	1" Male	Spud	275
	-	3/4" Female	Spud	277
	-	1" Female	Spud	125
	12,5	-	Hosetail with Gasket	250
	20	-	Hosetail with Gasket	816
	25	-	Hosetail with Gasket	6153
	-	-	Wing Nut	782
	-	-	Gasket	252
50mm Screw Type	-	2" Male	Spud	1434
	-	2" Female	Spud	5147
	50	-	Hosetail with Gasket	711
	50	-	Shouldered Hosetail	8728
	-	-	Wing Nut	1378
	-	-	Gasket	710