



## CLAW COUPLINGS - UNIVERSAL

### Specifications

Universal Claw Couplings are manufactured in accordance with DIN Specifications.

These Couplings have a double-lock feature.

Hoses of different sizes can be coupled without the use of adaptors. These couplings can be used for compressed air, water and other.

Maximum working pressure of 10 Bar

### Materials of Construction

<b>Body</b>	Malleable cast iron
<b>Gasket</b>	Neoprene
<b>Coating</b>	Acid zinc plated and clear passivated

Male Spud



Female Spud



Hosetail



Hose Size (mm)	Pipe Thread B.S.P	Description	Item Number
-	1/2" Male	Spud with Gasket	MUL-1003
-	3/4" Male	Spud with Gasket	MUL-1004
-	1" Male	Spud with Gasket	MUL-1005
-	3/8" Female	Spud with Gasket	MUL-902
-	1/2" Female	Spud with Gasket	MUL-903
-	3/4" Female	Spud with Gasket	MUL-904
-	1" Female	Spud with Gasket	MUL-905
6		Hosetail with Gasket	MUL-701
10		Hosetail with Gasket	MUL-703
12,5		Hosetail with Gasket	MUL-704
20		Hosetail with Gasket	MUL-706
25		Hosetail with Gasket	MUL-707
-		Gasket	REF1601